



- MASTER VOLUME PUSH-PULL SWITCH DESIGNATED "MVS" SHOWN IN "OUT" POSITION, PUSH IN FOR PURE SOUND.
- DIAGNOSE TYPICAL WHT SIGNAL REQUIRED FOR 10 WATT OUTPUT AND (300 MV) REVERB INPUT COIL DRN.
- SIX DIGIT NUMBERS ARE FENDER PART NUMBERS.
- ALL CAPACITORS AT LEAST 600V, W.V.DC.
- ALL RESISTORS 1/2 WATT ±10%.
- VOLTAGES READ TO GROUND WITH V.T.V.M. NO SIGNAL, V5 (ONLY) VOLTAGES READ WITH "SPEED & INTENSITY" MAX. & VIBRATO ON.

CAUTION:
 100 VOLTS AVAILABLE - DISCONNECT POWER SUPPLY AND ALLOW AT LEAST 30 SECONDS FOR VOLTAGES TO BLEED-OFF, BEFORE SCREWING AMPLIFIER.

100 TO 260 V
 EXPORT VERSIONS
 ONLY (50/60 Hz)

Fender/Rhodes/Rhodes

135 WATT 15 AMP
 W/REVERB AND VIBRATO

103694

VERB. REV.	VERB. REV.
REVERB	REVERB
REVERB	REVERB
REVERB	REVERB
REVERB	REVERB
REVERB	REVERB